

PATENT



IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants: RON KALIAN ET AL.

Serial No.: 09/780,036

Filed: February 9, 2001

Confirmation No. 8407

Group Art Unit: 2661

Examiner: Ian N. Moore
Technology Center 2600

RECEIVED

DEC 07 2004

Title: A METHOD OF SYNCHRONIZING THE REPLAY OF AUDIO DATA IN A
NETWORK OF COMPUTERS

SUBMISSION OF PRIORITY DOCUMENT

COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, VA 22313-1450


S I R :

Enclosed is a certified copy of the corresponding British patent application for
which priority is claimed under 35 USC 119.

<u>Country</u>	<u>Application No.</u>	<u>Filing Date:</u>
GREAT BRITAIN	0003054.4	February 11, 2000

No fee is believed to be due with this submission. However, if any fees are due,
please charge any required fee (or credit any overpayments of fees) to the Deposit
Account of the undersigned, Account No. 500601 (Docket no 722-X01 -004).

Respectfully submitted,



Martin Fleit, Reg. #16,900

Enclosures

Martin Fleit
FLEIT KAIN GIBBONS GUTMAN BONGINI & BIANCO
601 Brickell Key Drive Suite 404
Miami, Florida 33131
Tel: 305-416-4490; Fax: 305-416-4489
e-mail: MFleit@FleitKain.com



PATENT

Attorney Docket No: 722-X01-004

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Inventors: RON KALIAN et al
Serial No.: 09/780,036
Filed: February 9, 2001
Title: A METHOD OF SYNCHRONIZING THE REPLAY OF
AUDIO DATA IN A NETWORK OF COMPUTERS


CERTIFICATE OF EXPRESS MAILING

PATENTS

EXPRESS "Express Mail" Mailing Label number EV333611771 US

Date of November 23, 2004

I hereby certify that the attached paper(s) or fee(s) is/are being deposited with the United States Postal Services "Express Mail Post Office to Addressee" service under 37 CFR §1.10 on the date indicated above and is addressed to the Commissioner for Patents, P.O.Box 1450, Alexandria, VA 22313-1450.


(Signature of person mailing paper or fee)

ANGELLA JOHNSON

(Typed or printed name of person mailing paper or fee)

USSIN 09/780,036

A1U 2661



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1985 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., p.l.c. (L.C.) or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.


Signed

Dated: 20 March 2001

CERTIFIED COPY OF

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



11FEB00 E512409-1 002747

1/7700 0.00-0003054.4

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference

PV002

2. Patent application number

(The Patent Office will fill in this part)

0003054.4

11 FEB 2000

3. Full name, address and postcode of the or of each applicant (underline all surnames)

Purple Voice Limited
Dawley Road
Hayes
Middlesex UB3 1HH

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

7704737001
England

4. Title of the invention

A method of synchronising the replay of audio data in a network of computers

5. Name of your agent (if you have one)

QED I.P. Services Limited

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Dawley Road
Hayes
Middlesex UB3 1HH

Patents ADP number (if you know it)

7634173001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 6

Claim(s) 1

Abstract 1

Drawing(s) 2 + 2

10. If you are also filing any of the following, state how many against each item.

Priority documents -

Translations of priority documents -

Statement of inventorship and right to grant of a patent (Patents Form 7/77) -

Request for preliminary examination and search (Patents Form 9/77) 1 ✓

Request for substantive examination (Patents Form 10/77) -

Any other documents (please specify) -

11.

I/We request the grant of a patent on the basis of this application.

Signature

Alan C Sharp

Date

10/2/00

12. Name and daytime telephone number of person to contact in the United Kingdom

Dr Alan Sharp

0181-848-6490

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

A METHOD OF SYNCHRONISING THE REPLAY OF AUDIO DATA IN A NETWORK OF COMPUTERS

5 This invention relates to a method of synchronising the replay of audio data in a network of computers.

Concomitant with the increased popularity of the Internet and intranets in recent years, there has been interest in combining digital data transmission with voice and other audio program content, including Internet radio, internet
10 telephony, voice-mail, and unified messaging. In many businesses, such as financial dealing rooms, each person has a networked computer on their desk in addition to a telephone connected to a telecommunications system.

A problem arises with such systems when a message containing audio data is sent simultaneously to a number of such networked computers within earshot
15 of one another. The data is sent over the network as a series of data packets, which are reassembled at the destination computer and replayed. It is in the nature of such networks that the time taken for each data packet to travel over the network will be slightly different, depending on a number of factors such as how busy the network is at that time. Thus neighbouring computers can get their
20 audio replay out of synchronisation, which can be annoying for the listener.

Some of the reasons for a loss of synchronisation are:-

1. Routing Variations - packets from a source (server) to a destination (client) may take different routes across the network, thus resulting in different arrival times at different clients and/or loss of packet order.
- 25 2. Timebase Errors (Jitter) - even if packets travelled the same route between server and client, there would be variations in arrival times due to network load and other uncontrollable factors.
3. Error Correction - clients need to employ protocols to maximise the reliability of data transmission to deal with problems such as packet loss, corruption of
30 data packets, and loss of order. These can involve further processing and

possible retransmission, which result in delays which exacerbate the above problems.

4. Client Hardware – different client hardware can cause a given packet to be processed at different speeds by different clients. Also, different sound processors may have calibration errors resulting in up to 3% variation in playback speed.
5. Client Software – different operating systems and/or system configuration parameters and/or applications run in parallel with the voice client may cause further variations in replay speed and thus give rise to a lack of synchronisation of clients within earshot of one another.

An object of the present invention is to mitigate this problem.

According to a the invention there is provided a method as specified in the claims.

- 15 Methods for achieving multiparty synchronisation for real time network application have been described in US 5,682,384. However, these methods describe systems in which data from a plurality of sources arrives at a single destination station or client. The present invention concerns a different problem – that of lack of synchronisation where data from a single source arrives at a plurality of neighbouring destination stations or clients.

- Embodiments of the invention will now be described, by way of example only, with reference to the accompanying schematic drawings, in which:-
- Figure 1 shows flow diagram of a method according to the invention,
- 25 Figure 2 shows a block diagram of a client-server network, and
 - Figure 3 shows a further client –server network,

In computer networks using audio data, such as for example in dealing rooms, there are several forms of real time communications. They are:

Broadcast – point to many simplex communications, this is typically used to transfer information – e.g. “Pepsi have bought 3 extra bottling plants in the UK their share price is expected to go unchanged”

Intercom – typically point to point full duplex calls over ambient speakers, though
 5 typically the information is half duplex or question and answer – e.g. “What is the Dollar Franc rate?” or “Fred your visitor is in reception?”

Hoot and Holler – multipoint to multipoint conference, where again information is being disseminated and multiple people within a company will wish to communication to a large number of listeners around the world on the same
 10 subject. This is typically product related.

Although today most of the communication is simply voice only, the ability to communicate with the addition of real time video and associated data (files, research, documentation) is desirable.

In order to implement efficient communications a central sever is used with
 15 Broadcasts and Hoots to combine any incoming voice and data streams and routes the combined streams to intended recipients. An example of a network topology allowing this functionality is shown in Figure 2. This figure shows a network backbone (5), such as for example an Ethernet cable, coupled to a plurality of workstation computers (6) and a server (7). This is a typical example
 20 of a client-server architecture. With such a network topology it would be normal practice to have the server (7) control the data traffic in an analogous way to the central exchange (2) shown in Figure 1, with the workstation computers (6) acting in an analogous way to the telephones (3) in Figure 1.

To generate an input to a broadcast or an existing hoot in a system as
 25 shown in Figure 2, each “push to talk” voice data stream (and any video or other data) is routed from the workstation to the server, which then broadcasts a combined hoot voice stream to predefined workstations. The server can conveniently store the combined stream for later replay.

In one example of such a system, described in our co-pending patent
 30 application number GB 9916871.8, the communication system has a first server

function that keeps track of permissions and usage and a second server function that combines voice streams or other data streams for broadcast and which provides storage means for storing the same data streams. The system also comprises a plurality of workstation computers each of which exchanges data on its intercom usage with the first server function, but which sends the intercom voice stream directly to the other workstation computer. Each workstation computer includes data storage means for storing the intercom voice stream for that particular workstation, such that the first server function is both able to keep track of intercom usage and subsequently to arrange for playback at any authorised point of any intercom message. The first and second server functions may be combined in a single server, or may be provided by separate servers.

Figure 3 shows such a system in which both server functions are combined in a single server (10). This server has a part (11) which is allocated to store broadcast messages including audio data such as voice. The workstations (12) each have a data store (14) for storing intercom messages including audio data such as voice. It is within the scope of the present invention for each workstation to store any combination of its own outgoing and incoming intercom data streams. To reduce storage requirements, the two data streams may be combined, for example by summing the two channels and storing this summed data, or by using other forms of compression appropriate for the type of data.

The system implements broadcasts and hoots as follows. A person at a workstation computer (12) authorised to send such a message provides data to a routing server (10), usually in the form of data packets. These packets are combined into a single audio data stream at the server, which then sends the data stream out to a given subset of the workstations as a broadcast message, and stores this data in part 11. The broadcast message is then replayed by all the workstations participating in that particular hoot.

An example of an embodiment of a method according to the present invention is shown schematically in the flow diagram of Figure 1. The following discussion assumes that data corresponding to voice messages is sent in variable sized packets. The packets received at the destination station are identical to those

sent from the source station, and the packets are received in the same order in which they were sent. If any of these conditions are not met, known techniques can be employed to minimise voice loss.

Block 20 denotes the start of the process. Block 21 denotes receiving a voice packet at a destination station over a network. Block 22 denotes deciding whether the received voice packet is the first of a voice spurt (i.e. the first packet in a connection or one preceded by non-voice packets). If it is the first, Block 23 denotes storing the time it was received as the "start time". Block 24 denotes deciding whether the voice packet has arrived at the expected time, or whether it is late or early. If it arrives at the expected time, or is the first packet of a voice spurt (received at the "start time"), then Block 30 denotes waiting, so that the packet is sent to the sound playing device (denoted by Block 31) with a predetermined delay time after the "start time". If the decision at Block 24 is that it has not arrived at the expected time, Block 25 denotes deciding whether it has arrived later (shown as $d > 0$) or earlier (shown as $d < 0$) than expected.

If it has arrived earlier than expected, in a conventional replay system it would just be delayed for a bit longer before replay. However, one possibility is that the "start time" for the destination station being considered was later than its neighbours due to routing or other delays. Under such conditions, neighbouring destination stations would start replaying the voice at different times. In the present invention, Block 27 denotes determining a corrected "start time", either by subtracting the amount of time by which the voice packet has arrived earlier than expected from the original "start time", or by calculating a mean or average "start time" to be used in place of the original "start time".

If the voice packet has arrived later than expected, but before it should be played, then it is placed in the queue with a shorter delay time. If the mean or average "start time" is being used rather than the minimum time, it must be recalculated, taking into account this longer arrival time.

The voice data is stored in a FIFO buffer prior to being sent to the sound replay device. Block 26 denotes deciding upon what to do when this buffer becomes empty of voice data (sometimes known as an undervoice condition).

Block 29 denotes resetting the start time and waiting for a new voice spurt to begin. If the buffer is not empty, it is possible that it might become too full and over flow. If that happens, Block 28 denotes removing excess voice data. There are known techniques for performing this task, such as removing silences or playing
5 the voice data faster in real time. Blocks 30 and 31 have the same meanings as before.

Apparatus for putting the present invention into effect can comprise a suitably programmed general purpose computer, including a sound card or other sound output means.

10 Finally, the accompanying abstract is hereby incorporated by reference.

CLAIMS

1. A method of synchronising the replay of audio data sent as data packets in a
5 network of computers, the audio data being sent from a source station to a plurality of destination stations within earshot of one another, each data packet setting out from the source station to respective destination stations at substantially the same time, each packet taking a travel time to reach its destination station, the travel times having a substantially random distribution
10 over a range of times, the method including determining the mean travel time of a packet, and providing a delay between the time a given packet is sent and its replay, the delay being adapted such that it corresponds to a predetermined time equal to said mean travel time plus a constant time.
2. A method of synchronising the replay of audio data sent as data packets in a
15 network of computers, the audio data being sent from a source station to a plurality of destination stations within earshot of one another, each data packet setting out from the source station to respective destination stations at substantially the same time, each packet taking a travel time to reach its destination station, the travel times having a distribution over a range of
20 times, the method including determining the minimum travel time of a packet, and providing a delay between the time a given packet is sent and its replay, the delay being adapted to vary such that it corresponds to a predetermined time equal to said minimum travel time plus a constant time.
3. A method as claimed in any preceding claim in which the distribution is a
25 normal distribution.
4. A method as claimed in any preceding claim in which the predetermined time is sufficiently long for several data packets to have arrived at the destination station before the value of the delay and/or mean travel time and/or
30 minimum travel time is computed.

ABSTRACT**A METHOD OF SYNCHRONISING THE REPLAY OF AUDIO DATA IN A
NETWORK OF COMPUTERS**

5

A method of synchronising the replay of audio data sent as data packets in a network of computers is described. The audio data passes from a source station to destination stations within earshot of one another, and each data packet sets out
10 from the source station to respective destination stations at substantially the same time, taking a travel time to reach its destination station. The travel times are distributed over a range of times, and are difficult to predict. The method includes determining the mean travel time (or minimum travel time) of a data packet, and providing a delay between the time a given packet is sent and its replay, the delay
15 being adapted such that it corresponds to a predetermined time equal to the mean travel time (or minimum travel time) plus a variable time. This results in the synchronisation of audio data replay, because the mean travel time (or minimum travel time) is approximately the same for neighbouring destination stations, on average.

20

(Figure 4).




Figure 1

2/2




Fig 2.




Fig 3.